



# DCN-IPR8BZANZ-PRO-11

8MP IR Motorized Varifocal Bullet Network Camera



## Key Features

- 1/2.8" STARVIS™ CMOS
- Max. 8MP(3840 × 2160) @25/30 fps resolution
- 2.7 to 13.5 mm motorized lens
- True WDR, 3D DNR, ROI, HLC, BLC, Defog
- Support face, human, vehicle detection and capture
- Intelligent analytics: intrusion, single line crossing, double line crossing, loitering, wrong-way detection, smart motion detection, and people counting
- Smart IR distance up to 40 m
- 1/1 audio input/output, 1/1 alarm input/output
- Built-in micro SD card slot
- IP67 protection


## Specification

| Camera                                                                                                                                                                                                                                                                     |                                                                                                                                                                                             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor                                                                                                                                                                                                                                                               | 1/2.8" Progressive Scan CMOS                                                                                                                                                                |
| Max. Resolution                                                                                                                                                                                                                                                            | 8MP, 3840(H) × 2160(V)                                                                                                                                                                      |
| Electronic Shutter                                                                                                                                                                                                                                                         | Auto/Manual, 1/5 to 1/20,000 s                                                                                                                                                              |
| Min. illumination                                                                                                                                                                                                                                                          | Color: 0.01 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR                                                                                                                                        |
| Day & Night                                                                                                                                                                                                                                                                | IR cut filter                                                                                                                                                                               |
| Wide Dynamic Range                                                                                                                                                                                                                                                         | True WDR                                                                                                                                                                                    |
| Angle Adjustment                                                                                                                                                                                                                                                           | Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°                                                                                                                                      |
| Lens                                                                                                                                                                                                                                                                       |                                                                                                                                                                                             |
| Lens Type                                                                                                                                                                                                                                                                  | Varifocal lens, Motorized focal                                                                                                                                                             |
| Iris                                                                                                                                                                                                                                                                       | Fixed Iris                                                                                                                                                                                  |
| Focal Length                                                                                                                                                                                                                                                               | 2.7 to 13.5 mm                                                                                                                                                                              |
| Max. Aperture                                                                                                                                                                                                                                                              | F1.6                                                                                                                                                                                        |
| Field of View (FOV)                                                                                                                                                                                                                                                        | H: 102.7° to 30.2°, V: 53.8° to 16.8°                                                                                                                                                       |
| DORI Distance                                                                                                                                                                                                                                                              |                                                                                                                                                                                             |
| Detect                                                                                                                                                                                                                                                                     | 88 to 280 m (288.7 to 918.6 ft)                                                                                                                                                             |
| Observe                                                                                                                                                                                                                                                                    | 35.2 to 112 m (115.5 to 367.5 ft)                                                                                                                                                           |
| Recognize                                                                                                                                                                                                                                                                  | 17.6 to 56 m (57.7 to 183.7 ft)                                                                                                                                                             |
| Identify                                                                                                                                                                                                                                                                   | 8.8 to 28 m (28.9 to 91.9 ft)                                                                                                                                                               |
| DORI (Detect, Observe, Recognize, and Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. |                                                                                                                                                                                             |
| Illuminator                                                                                                                                                                                                                                                                |                                                                                                                                                                                             |
| Illuminator Type                                                                                                                                                                                                                                                           | IR                                                                                                                                                                                          |
| Illumination Distance                                                                                                                                                                                                                                                      | Up to 40 m (131.2 ft)                                                                                                                                                                       |
| Illumination On/Off Control                                                                                                                                                                                                                                                | Auto/Manual                                                                                                                                                                                 |
| IR wavelength                                                                                                                                                                                                                                                              | 850 nm                                                                                                                                                                                      |
| Intelligent Analytics                                                                                                                                                                                                                                                      |                                                                                                                                                                                             |
| Multi-Object Detection                                                                                                                                                                                                                                                     | Supports face, human, vehicle detection and capture.<br>Supports multiple frame modes: Full Frame, Four-corner Frame, and Mosaic.                                                           |
| Intelligent Analysis                                                                                                                                                                                                                                                       | Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way detection, and Smart motion detection<br>Support alarm triggering by specified target types (human and vehicle) |

|                        |                                                                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| People Counting        | Support                                                                                                                                                                                |
| <b>Video and Audio</b> |                                                                                                                                                                                        |
| Streaming Capability   | 3 Streams                                                                                                                                                                              |
| Stream/Frame Rate      | Stream1: 3840 × 2160, 2592 × 1944, 2592 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080, 1280 × 720 @25/30 fps<br>Stream2: D1, VGA, CIF @25/30 fps<br>Stream3: VGA, CIF, QVGA @25/30 fps |
| Bit Rate Control       | CBR/VBR                                                                                                                                                                                |
| Bit Rate               | Stream1: 200 kbps to 16 Mbps<br>Stream2: 100 kbps to 6 Mbps<br>Stream3: 100 kbps to 3 Mbps                                                                                             |
| Region of Interest     | Off/On (8 areas, Rectangle)                                                                                                                                                            |
| Smart Encode           | Support                                                                                                                                                                                |
| Audio Compression      | G.711 A-law, G.711 μ-law, RAW PCM                                                                                                                                                      |
| Audio Bit Rate         | 64 Kbps (G.711), 128 Kbps (RAW_PCM)                                                                                                                                                    |
| <b>Image</b>           |                                                                                                                                                                                        |
| Image Adjustment       | Brightness, Sharpness, Contrast, Saturation adjustable                                                                                                                                 |
| Scene Setting          | Indoor, Outdoor, Mirror, Corridor Mode                                                                                                                                                 |
| Exposure Mode          | Auto, Manual, Shutter priority                                                                                                                                                         |
| White Balance          | Auto, Tungsten, Fluorescent, Daylight, Shadow, Manual                                                                                                                                  |
| Day/Night Setting      | Auto, Day, Night, Timer                                                                                                                                                                |
| Noise Reduction        | 2D/3D DNR                                                                                                                                                                              |
| Image Enhancement      | WDR, HLC, BLC, Defog                                                                                                                                                                   |
| Privacy Masking        | 4 areas                                                                                                                                                                                |
| <b>Event</b>           |                                                                                                                                                                                        |
| Alarm Triggers         | IVS, Motion detection, Alarm input, Network alarm, Disk alarm, Day/Night switch alarm, Abnormal sound detection                                                                        |
| Event Actions          | Alarm record, SMTP upload, FTP upload, Alarm output, Audible alarm output                                                                                                              |
| <b>Network</b>         |                                                                                                                                                                                        |
| Protocols              | IPv4/IPv6, HTTP/HTTPS, DNS, DDNS, DHCP, PPPoE, RTSP/ RTCP/RTP, TCP/UDP, NTP, ARP, UPnP, FTP, SMTP, QoS, ICMP, IGMP, SMTP, 802.1x, SNMP, Multicast                                      |
| Interoperability       | ONVIF (Profile S/T/G/M), SDK, CGI                                                                                                                                                      |
| Max Concurrent Streams | 10 channels                                                                                                                                                                            |
| User/Host Level        | 32+ users, 3 levels: Administrator, Operator, Media user                                                                                                                               |
| Security               | IP address filter, HTTPS, Illegal login lock, IEEE 802.1x                                                                                                                              |

|                       |                                                                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Web Viewer            | <IE11, Chrome, Firefox, Microsoft Edge                                                                                                             |
| <b>Interface</b>      |                                                                                                                                                    |
| Network Interface     | 1 Ethernet (10/100 Base-T) RJ-45 Connector                                                                                                         |
| Audio Interface       | 1ch Input, 1ch Output                                                                                                                              |
| Alarm Interface       | 1ch Input, 1ch Output                                                                                                                              |
| SD Card Slot          | Built-in, up to 256GB                                                                                                                              |
| Reset Button          | Support                                                                                                                                            |
| <b>General</b>        |                                                                                                                                                    |
| Language              | English, Chinese, Traditional Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian, Japanese, Korean. Default: English |
| Power Supply          | 12 VDC (-15% to +25%)/PoE (802.3af)                                                                                                                |
| Power Consumption     | Max 9.5 W                                                                                                                                          |
| Operating Temperature | -40°C to 55°C (-40°F to 131°F )                                                                                                                    |
| Operating Humidity    | Less than 90% RH                                                                                                                                   |
| Ingress Protection    | IP67                                                                                                                                               |
| Certifications        | CE-EMC<br>- EN 55032, EN IEC 61000-6-3, EN IEC 61000-3-2, EN 61000-3-3, EN 55035, EN 50130-4<br>FCC 47 CFR Part 15 Subpart B                       |
| Material              | Aluminum alloy                                                                                                                                     |
| Dimensions            | 232 × 80 × 80 mm (9.13 × 3.15 × 3.15 inch)                                                                                                         |
| Net Weight            | 0.81 kg (1.79 lb)                                                                                                                                  |

## Dimensions (mm)



## Accessories

### Optional:



SN-CBK656A  
Junction Box



SN-CBK627D  
Pole Mount